

SUBARU (EU) LEGACY / OUTBACK BC, BJ, BF LEGACY / OUTBACK 2.0 (1992-1994)



ENGINE EJ20
Capacity: 4,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

Change every 12500 km/ 6 months

DIFFERENTIAL FROM AUTOMATIC
Capacity: 1,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071

Check every 25000 km/ 12 months, change every 50000 km/ 24 months

TRANSAXLE MANUAL 5/1
Capacity: 3,3 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

Check every 25000 km/ 12 months, change every 50000 km/ 24 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Gearlube RPC 75W-80

Check every 25000 km/ 12 months, change every 50000 km/ 24 months

TRANSMISSION AUTOMATIC 4/1
Capacity: 8,3 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 25000 km/ 12 months, change every 50000 km/ 24 months

SUBARU (EU) LEGACY / OUTBACK BC, BJ, BF LEGACY / OUTBACK 2.0 (1992-1994)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 50000 km/ 24 months

POWER STEERING

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 6,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 50000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.