

SUBARU (EU) TRIBECA (B9) TRIBECA (2006-2008)



ENGINE EZ30
Capacity: 5,7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Duranza LSP 5W-30

PRODUCT RECOMMENDATION 3

Asyntho 5W-30

Change every 15000 km/ 12 months

DIFFERENTIAL FRONT (4x4)
Capacity: 1,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Gearlube RPC 75W-80

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

DIFFERENTIAL REAR (4x4)
Capacity: 0,8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Gearlube RPC 75W-80

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

TRANSMISSION AUTOMATIC 5/1
Capacity: 9,8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

HYDRAULIC BRAKE SYSTEM

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

Check every 24 months/ 30000 km

SUBARU (EU) TRIBECA (B9) TRIBECA (2006-2008)



POWER STEERING

Capacity: 0,8-0,9 liter

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM

Capacity: 7,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Change every 30000 km/ 24 months

COOLING SYSTEM MY 2009

Capacity: 7,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Change every 120000 km/ 72 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km/ 24 months, change every 220000 km/ 132 months

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.