SUBARU (EU) VIVIO VIVIO (1997-1998)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40

Change every 12500 km/ 12 months

TRANSAXLE CVT 1/1 Capacity: 2,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Change every 50000 km/24 month	78	-

TRANSAXLE MANUAL 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90
Change every 50000 km/24 month)S	-

HYDRAULIC BRAKE SYSTEM

Normal

PRODUCT RECOMMENDATION 1

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Drauliquid-LV Super DOT 4

Drauliquid-S DOT 4

Drauliquid DOT 3

Check every 25000 km/12 months, change every 50000 km/24 months

COOLING SYSTEM Capacity: 3,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 50000 km/ 24 months	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

SUBARU (EU) VIVIO VIVIO (1997-1998)



information contained herein is subject to changes without notification.