

SUZUKI ALTO ALTO SB 308 (1985-1994)**ENGINE F8B**

Capacity: 2,7 liter, Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Change every 10000 km/ 6 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 5000 km/ 4 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Change every 5000 km/ 4 months***TRANSAXLE AUTOMATIC 3/1**

Capacity: 3,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 10000 km/ 6 months, change every 40000 km/ 24 months***TRANSAXLE MANUAL 4/1**

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 1081

PRODUCT RECOMMENDATION 3

SP Gear 5015*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

SUZUKI ALTO ALTO SB 308 (1985-1994)**HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 40000 km/ 48 months***COOLING SYSTEM**

Capacity: 3,6-3,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Change every 40000 km/ 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.