SUZUKI SPLASH SPLASH 1.0 A5B310 (2011-2015)



ENGINE K10B Capacity: 3,1-3,2 liter (Dry fill), Capacity: 2	,9-3 liter (Service fill), Filter capacity: 0,2 lite	r		
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 15W-40				
Change every 15000 km/ 12 months				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Asyntho 5W-30	Emperol 10W-40			
Change every 15000 km/ 12 months				
USE		CLIMATE		
Severe		Mediterranean		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 15W-40				
Change every 7500 km/ 6 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Asyntho 5W-30	Emperol 10W-40			
Change every 7500 km/ 6 months				
TRANSAXLE MANUAL 5/1 Capacity: 2,2 liter				
USE		CLIMATE		
Preferred		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 5015				
Check every 45000 km/ 36 months, change every 150000 km/ 120 months				
USE		CLIMATE		
Preferred, first check only		Moderate		
PRODUCT RECOMMENDATION 1				

SP Gear 5015

Check every 15000 km/ 12 months

SUZUKI SPLASH SPLASH 1.0 A5B310 (2011-2015)



use Alternative (acceptable)		climate Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90		
Change every 45000 km/ 36 months				
USE		CLIMATE		
Alternative, severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90		
Check every 15000 km/ 12 months, change every 30000 km/ 24 months				
USE		CLIMATE		
Preferred, severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 5015				

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 30000 km/ 24 months				

Check every 15000 km/ 12 months, change every 75000 km/ 60 months

SUZUKI SPLASH SPLASH 1.0 A5B310 (2011-2015)



COOLING SYSTEM Capacity: 4,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Change every 75000 km/ 48 months		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Change every 150000 km/ 96 months		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 14+	Coolant -38 Organic NF	
Change every 45000 km/ 36 months		

AIRCONDITIONING COMPRESSOR

Capacity: 80-100 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 350-390 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.