SUZUKI SWIFT SF SWIFT 1.0 SF310 (1989-1993)



| ENGINE G10A Capacity: 3,3 liter, Filter capacity: 0,3 liter | | |
|--|---|---|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Bi-Turbo 20W-50 | | |
| Change every 10000 km/ 6 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Emperol 10W-40 | Classic Racing Oil 15W-50 | Bi-Turbo 15W-40 |
| Change every 10000 km/ 6 months | | |
| USE | | CLIMATE |
| Severe | | Mediterranean |
| | | |
| PRODUCT RECOMMENDATION 1 | | |
| | | |
| PRODUCT RECOMMENDATION 1 | | |
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 | | CLIMATE |
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 5000 km/ 4 months | | |
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 5000 km/ 4 months USE | PRODUCT RECOMMENDATION 2 | CLIMATE |
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 5000 km/ 4 months USE Severe | PRODUCT RECOMMENDATION 2 Classic Racing Oil 15W-50 | climate Moderate |
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 5000 km/ 4 months USE Severe PRODUCT RECOMMENDATION 1 | | CLIMATE Moderate PRODUCT RECOMMENDATION 3 |
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 5000 km/ 4 months USE Severe PRODUCT RECOMMENDATION 1 Emperol 10W-40 | | CLIMATE Moderate PRODUCT RECOMMENDATION 3 |

| TRANSAXLE AUTOMATIC 3/1 Capacity: 3,5 liter | | |
|--|---|----------|
| USE | (| CLIMATE |
| Normal | 1 | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |
| | | |

Check every 10000 km/ 6 months, change every 160000 km/ 96 months

| USE | CLIMATE |
|----------------------------------|----------|
| Severe | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| ATF Dexron II-D | |
| Change every 20000 km/ 12 months | |

SUZUKI SWIFT SF SWIFT 1.0 SF310 (1989-1993)



| TRANSAXLE MANUAL 5/1 Capacity: 2,4 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |

Check every 10000 km/ 6 months, change every 20000 km/ 12 months

| HYDRAULIC BRAKE SYSTEM | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |
| Observed and 00000 line (10 man 1/h a | |

Change every 80000 km/ 48 months

| POWER STEERING Capacity: 0,7 liter | |
|---------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| ATF Dexron II-D | |
| | |

Check every 10000 km/ 6 months

| COOLING SYSTEM Capacity: 3,9-4 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |
| Change every 40000 km/ 48 months | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.