SUZUKI SWIFT SF SWIFT 1.3 SF413 (1994-2000)



ENGINE G13BA Capacity: 3,3 liter, Filter capacity: 0,3 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Check every 3000 km, change every 1000	00 km/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

Check every 3000 km, change every 10000 km/ 12 months

TRANSAXLE AUTOMATIC 3/1 Capacity: 3,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Check every 10000 km/ 12 months, change every 160000 km

TRANSAXLE MANUAL 5/1 Capacity: 2,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Charles a variet 40000 km² / 40 magnitha	change every 40000 km/ 49 months	

Check every 10000 km/ 12 months, change every 40000 km/ 48 months

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 10000 km/ 12 months, chang	e every 40000 km/ 24 months	

SUZUKI SWIFT SF SWIFT 1.3 SF413 (1994-2000)



POWER STEERING AS OPTION Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 10000 km/ 12 months	

COOLING SYSTEM Capacity: 4,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	

Check every 10000 km/12 months, change every 40000 km/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.