TATA INDICA EV2 INDICA EV2 1.4 TURBO DIESEL (CR4) (2011-2018)



ENGINE Tata 1.4 (CR-4) Capacity: 5,5 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Bi-Turbo 15W-40	
Change every 10000 km/ 12 months	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	
Change every 10000 km/ 12 months	

TRANSAXLE MANUAL TA 65 5/1 Capacity: 3,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 20000 km		

HYDRAULIC BRAKE SYSTEM Capacity: 0,27 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Charle avery 10000 km, shanga avery	10000 km/24 months		

Check every 10000 km, change every 40000 km/24 months

POWER STEERING Capacity: 1,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Change every 80000 km			

TATA INDICA EV2 INDICA EV2 1.4 TURBO DIESEL (CR4) (2011-2018)



COOLING SYSTEM Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 40000 km/ 24 month	78	1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.