THE LONDON TAXI COMPANY TX TX4 EURO 5 (2012-2015)



| CLIMATE |
|----------|
| Moderate |
| |
| |
| |

Change every 12000 miles

| DIFFERENTIAL REAR Capacity: 1,8 liter | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |
| Check every 10000 miles, change every 60000 miles | | |
| USE | | CLIMATE |

| USE | CLIMATE |
|--------------------------|----------|
| First change only | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube LS 80W-90 | |
| Change every 3000 miles | |

| TRANSMISSION AUTOMATIC DCX 5/1 Capacity: 9 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 4026 | |
| Change every 36000 miles | |

Jnange every 36000 miles

THE LONDON TAXI COMPANY TX TX4 EURO 5 (2012-2015)



| TRANSMISSION MANUAL Eaton FSO-2405A 5/1 Capacity: 3 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |
| Check every 10000 miles, change every 60000 miles | | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |
| Change every 12000 miles | | |

| HYDRAULIC BRAKE/CLUTCH SYST | EM | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| Charly sugged sugged sharpe sugged 20000 miles/24 mention | | |

Check every 1 weeks, change every 30000 miles/24 months

| POWER STEERING | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 4026 | |

| COOLING SYSTEM Capacity: 7,3 liter | |
|---------------------------------------|-----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |
| Change every 100000 miles/ 24 months | · · · · · |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.