TOYOTA (EU) COROLLA E10 COROLLA 1.6I 16V (1992-1997)



ENGINE 4AFE Capacity: 3,3 liter, Filter capacity: 0,2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 10000 km/ 6 months		

TRANSAXLE AUTOMATIC 4/1 Capacity: 3,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Check every 20000 km, change ev	rery 40000 km/ 24 months	'

TRANSAXLE MANUAL 5/1 Capacity: 2,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Check every 20000 km/ 12 months	, change every 80000 km/ 48 months	,

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 10000 km/ 6 months, change every 40000 km/ 24 months		

TOYOTA (EU) COROLLA E10 COROLLA 1.6I 16V (1992-1997)



HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 10000 km/6 months, change every 40000 km/24 months

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 20000 km/ 12 months

COOLING SYSTEM Capacity: 5 liter, Capacity: 5,3 liter (+ airconditioning), Capacity: 5,8 liter (with automatic transmission)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 40000 km/ 48 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.