## TOYOTA (EU) COROLLA VERSO R1 COROLLA VERSO 2.2 D4-D-F (2005-2007)



ENGINE 2AD-FTV	5.0 liter (Service fill) Filter conscient 0.4 li	tor
Capacity: 6,7 liter (Dry fill), Capacity:	5,9 liter (Service fill), Filter capacity: 0,4 li	TEF CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 7500 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40
Change every 7500 km/ 6 months		
TRANSAXLE MANUAL EA63 6/1 Capacity: 2,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

PRODUCT RECOMMENDATION 2

**SP Gear 5015** 

Change every 60000 km/ 48 months

PRODUCT RECOMMENDATION 1

Check every 48 months/ 60000 km

USE

Severe

**SP Gear 1081** 

CLIMATE

Moderate

## TOYOTA (EU) COROLLA VERSO R1 COROLLA VERSO 2.2 D4-D-F (2005-2007)



HYDRAULIC BRAKE SYSTEM ABS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
01 000001 /04 /1		

Change every 30000 km/24 months

HYDRAULIC CLUTCH SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Oh I	'			

Check every 24 months/ 30000 km

POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Matic 2032	ATF Almirol	ATF Dexron II-D	
Oberthouse O.A. months / 00000 him			

Check every 24 months/ 30000 km

COOLING SYSTEM Capacity: 7,4-7,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

Check every 30000 km, change every 90000 km

USE	c	CLIMATE
First change only	N	Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 150000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.