

TOYOTA (EU) PRIUS + W4 PRIUS+ W4(2011-2019)



MOTOR 2ZR-FXE

Kapacitet: 4,2 liter (Servicepåfyldning), Kapacitet: 4,7 liter (Tør efterfyld), Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Foretrukne	Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Kraftig, foretrukket	Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

Skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Xedoz FE 5W-30

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Xedoz FE 5W-30

Skift alle 7500 km/ 6 måneder

TRANSAKSEL CVT P410 1/1

Kapacitet: 3,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 45000 km/ 36 måneder, skift alle 90000 km/ 72 måneder

TOYOTA (EU) PRIUS + W4 PRIUS+ W4(2011-2019)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 30000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 6,5 liter, Kapacitet: 6,9 liter (+ udstødningsvarmegenindvindingssystem)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 90000 km

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 150000 km

KØLESYSTEM INVERTER

Kapacitet: 2,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 90000 km

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 240000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.