

TOYOTA (EU) PRIUS W2 PRIUS THSD W2 (2006-2009)

**ENGINE 1NZ-FXE**

Capacity: 4,1 liter (Dry fill), Capacity: 3,7 liter (Service fill), Filter capacity: 0,3 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 15000 km/ 12 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Emperol 10W-40*Change every 15000 km/ 12 months*

USE

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 7500 km/ 6 months*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Emperol 10W-40*Change every 7500 km/ 6 months***TRANSAXLE HYBRID SYSTEM P112 1/1**

Capacity: 3,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 48 months/ 60000 km*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 45000 km/ 36 months, change every 90000 km/ 72 months*

TOYOTA (EU) PRIUS W2 PRIUS THSD W2 (2006-2009)



HYDRAULIC BRAKE SYSTEM ABS

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

COOLING SYSTEM COMBUSTION ENGINE

Capacity: 8,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 90000 km

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 150000 km

COOLING SYSTEM ELECTRIC DRIVE

Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 90000 km

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 150000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.