

TOYOTA (EU) RAV4 A4 RAV4 2.2 D-4D AWD DPF (2013-2015)



MOTOR 2AD-FTV

Kapacitet: 5,9 liter (Servicepåfyldning), Kapacitet: 6,3 liter (Tør efterfyld), Filterkapacitet: 0,4 liter

ANVEND

Normalt, svovlniveau i brændstof <50 ppm

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-30

PRODUKTANBEFALING 2

Avanza MSP 0W-30

PRODUKTANBEFALING 3

Presteza MSP 5W-30

Skift alle 15000 km/ 12 måneder

ANVEND

Alvorlig, svovlniveau i brændstof <50 ppm

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-30

PRODUKTANBEFALING 2

Avanza MSP 0W-30

PRODUKTANBEFALING 3

Presteza MSP 5W-30

Skift alle 7500 km/ 6 måneder

DIFFERENTIALE BAG

Kapacitet: 0,45-0,55 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

Skift alle 30000 km/ 48 måneder

REDUKTIONSGEARKASSE GF1A

Kapacitet: 0,4-0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

Skift alle 30000 km/ 48 måneder

TOYOTA (EU) RAV4 A4 RAV4 2.2 D-4D AWD DPF (2013-2015)



TRANSAXSEL AUTOMATISK U660F 6/1

Kapacitet: 2,8 liter (Servicepåfyldning), Kapacitet: 6,7 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 48 måneder/ 60000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 45000 km/ 36 måneder, skift alle 90000 km/ 72 måneder

TRANSAXSEL MANUEL EA64F 6/1

Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

Kontroller alle 48 måneder/ 60000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

Skift alle 60000 km/ 48 måneder

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 30000 km/ 24 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 30000 km/ 24 måneder

TOYOTA (EU) RAV4 A4 RAV4 2.2 D-4D AWD DPF (2013-2015)



KØLESYSTEM

Kapacitet: 7,3-7,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 90000 km

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 150000 km

KLIMAANLÆGSKOMPRESSOR R-134a

Kapacitet: 70 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM R-134a

Kapacitet: 470-530 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.