TOYOTA (EU) VERSO R1 VERSO 2.2 D-4D-F (2007-2009)



Capacity: 6,7 liter (Dry fill), Capacity: 5,9 liter (Service fill), Filter capacity: 0,4 liter use		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 months	5	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 7500 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40
Change every 7500 km/ 6 months		
TRANSAXLE MANUAL EA63 6/1		
Capacity: 2,3 liter		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	- Woderate
SP Gear 1081	SP Gear 5015	

PRODUCT RECOMMENDATION 2

SP Gear 5015

USE

Severe

SP Gear 1081

PRODUCT RECOMMENDATION 1

Change every 60000 km/48 months

CLIMATE

Moderate

TOYOTA (EU) VERSO R1 VERSO 2.2 D-4D-F (2007-2009)



HYDRAULIC BRAKE/CLUTCH SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Change every 30000 km/24 months

HYDRAULIC CLUTCH SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Obest and Amenda Amenda (2000) Inc.				

Check every 24 months/ 30000 km

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

COOLING SYSTEM Capacity: 7,4-7,6 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 30000 km, change every 90000 km				
USE		CLIMATE		
First change only		Moderate		
PRODUCT RECOMMENDATION 1				

Check every 30000 km, change every 150000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Coolant SP 14+