

TOYOTA (EU) VERSO S/ RACTIS XP12

VERSO S/ RACTIS 1.5 VVT-I (2013-2015)

**ENGINE 1NZ-FE**

Capacity: 4,1 liter (Dry fill), Capacity: 3,7 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Xedoz FE 5W-30	Asyntho 5W-30

Change every 15000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Xedoz FE 5W-30	Asyntho 5W-30

*Change every 7500 km/ 6 months***TRANSAXLE CVT K312 1/1**

Capacity: 6,42-7,47 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4016		

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4016		

*Check every 45000 km/ 36 months, change every 90000 km/ 72 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 30000 km/ 24 months

TOYOTA (EU) VERSO S/ RACTIS XP12

VERSO S/ RACTIS 1.5 VVT-I (2013-2015)

**COOLING SYSTEM**

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 30000 km, change every 90000 km

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 30000 km, change every 150000 km

AIRCONDITIONING COMPRESSOR R-134a

Capacity: 60-75 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 330-390 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.