

TOYOTA (USA / CAN) RAV4 XA20 RAV4 2.0 16V VVT-I 2WD (USA) ACA26 (2001-2001)



MOTOR 1AZ-FE

Kapacitet: 4,2 liter (Servicepåfyldning), Kapacitet: 4,9 liter (Tør efterfyld), Filterkapacitet: 0,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 7500 mil/ 6 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 5000 mil/ 4 måneder

TRANSAKSEL AUTOMATISK U241E 4/1

Kapacitet: 3,3 liter (Servicepåfyldning), Kapacitet: 8,6 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 30000 mil/ 24 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 30000 mil/ 24 måneder, skift alle 60000 mil/ 48 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 30000 mil/ 24 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 15000 mil/ 12 måneder, skift alle 30000 mil/ 24 måneder

TOYOTA (USA / CAN) RAV4 XA20 RAV4 2.0 16V VVT-I 2WD (USA) ACA26 (2001-2001)



HYDRAULISK BREMSESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 15000 mil/ 12 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 15000 mil/ 12 måneder

SERVOSTYRING

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 6,2 liter (med automatisk kraftoverføring), Kapacitet: 6,3 liter (med manuel transmission)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant SP 12 EVO		

Kontroller alle 15000 mil/ 12 måneder, skift alle 30000 mil/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.