

TOYOTA (USA / CAN) SEQUOIA SEQUOIA

4.7 V8 32V 4WD (USA) UCK45 (2000-2001)

**ENGINE 2UZ-FE**

Capacity: 7,1 liter (Dry fill), Capacity: 6,2 liter (Service fill), Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 7500 miles/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 5000 miles/ 4 months***DIFFERENTIAL FRONT**

Capacity: 1,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 15000 miles/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Change every 15000 miles/ 12 months*

TOYOTA (USA / CAN) SEQUOIA SEQUOIA

4.7 V8 32V 4WD (USA) UCK45 (2000-2001)

**DIFFERENTIAL REAR**

Capacity: 3,65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

Check every 15000 miles/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1
SP Gear 5015

PRODUCT RECOMMENDATION 2
Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3
SP Gear 1071

Check every 15000 miles/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

Change every 5000 miles/ 4 months

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1
SP Gear 5015

PRODUCT RECOMMENDATION 2
Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3
SP Gear 1071

Change every 5000 miles/ 4 months

TRANSFERBOX

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
SP Gear 1011

PRODUCT RECOMMENDATION 2
Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3
Syngear 75W-90

Check every 30000 miles/ 24 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1
SP Gear 1011

PRODUCT RECOMMENDATION 2
Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3
Syngear 75W-90

Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months

TOYOTA (USA / CAN) SEQUOIA SEQUOIA

4.7 V8 32V 4WD (USA) UCK45 (2000-2001)

**TRANSMISSION AUTOMATIC A340F 4/1**

Capacity: 12,3 liter (Dry fill), Capacity: 2 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 30000 miles/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

*Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

*Check every 15000 miles/ 12 months***POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

*Check every 15000 miles/ 12 months***COOLING SYSTEM**

Capacity: 11,7 liter, Capacity: 13,4 liter (+ rear heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.