

TOYOTA (USA / CAN) TUNDRA TUNDRA 4.0 V6 24V (USA) GSK50/51 (2011-2014)



MOTOR 1GR-FE

Kapacitet: 6,1 liter (Servicepåfyldning), Kapacitet: 6,9 liter (Tør efterfyld), Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

Skift alle 10000 mil/ 12 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

Skift alle 5000 mil/ 6 måneder

DIFFERENTIALE BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

Kontroller alle 15000 mil/ 18 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

Kontroller alle 15000 mil/ 18 måneder, skift alle 30000 mil/ 36 måneder

GEAR AUTOMATISK A750E 5/1

Kapacitet: 3 liter (Servicepåfyldning), Kapacitet: 10,5 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 30000 mil/ 36 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 30000 mil/ 36 måneder, skift alle 60000 mil/ 72 måneder

TOYOTA (USA / CAN) TUNDRA TUNDRA 4.0 V6 24V (USA) GSK50/51 (2011-2014)



HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 5000 mil/ 6 måneder

KØLESYSTEM

Kapacitet: 10,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 15000 mil/ 18 måneder, skift alle 50000 mil/ 60 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 15000 mil/ 18 måneder, skift alle 100000 mil/ 120 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.