

TOYOTA (USA / CAN) VENZA GGV10/15

VENZA 2.7 FWD (USA) AGV10 (2012-2012)

**ENGINE 1AR-FE**

Capacity: 5,3 liter (Dry fill), Capacity: 4,4 liter (Service fill), Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20

PRODUCT RECOMMENDATION 2

Duranza ECO 5W-20*Change every 5000 miles/ 6 months***TRANSAXLE AUTOMATIC U760E 6/1**

Capacity: 6,5 liter (Dry fill), Capacity: 3,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 30000 miles/ 36 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 5000 miles/ 6 months*

TOYOTA (USA / CAN) VENZA GGV10/15

VENZA 2.7 FWD (USA) AGV10 (2012-2012)

**COOLING SYSTEM**

Capacity: 7,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.