## TOYOTA (USA / CAN) AVALON XX10 AVALON 3.0 V6 (USA) MCX10 (1994-1996)



ENGINE 1MZ-FE Capacity: 4,7 liter (Service fill), Filter capacity: 0,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Change every 7500 miles/ 6 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Change every 5000 miles/ 4 months			

DIFFERENTIAL FROM AUTOMATIC Capacity: 0,85 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 15000 miles/ 12 months	

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 15000 miles/ 12 months	

TRANSAXLE AUTOMATIC 4/1 Capacity: 3,5 liter (Service fill)	
USE	
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
	•

Check every 30000 miles/24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months		

## PRODUCT RECOMMENDATION

## TOYOTA (USA / CAN) AVALON XX10 AVALON 3.0 V6 (USA) MCX10 (1994-1996)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 15000 miles/ 12 months		

\_\_\_\_\_

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 15000 miles/ 12 months

COOLING SYSTEM Capacity: 9,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 30000 miles/ 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.