TOYOTA (USA / CAN) AVALON XX20 AVALON 3.0 V6 (USA) MCX20 (1999-2002)



ENGINE 1MZ-FE Capacity: 4,7 liter (Service fill), Filter capacity: 0,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Change every 7500 miles/ 6 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Change every 5000 miles/ 4 months			

use Normal		climate Moderate
SP Matic 2032	ATF Almirol	ATF Dexron II-D

SP Matic 2032	ATF Almirol	ATF Dexron II-D	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Severe		Moderate	
USE		CLIMATE	

Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 15000 miles/ 12 months		

TOYOTA (USA / CAN) AVALON XX20 AVALON 3.0 V6 (USA) MCX20 (1999-2002)



POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 15000 miles/ 12 months

COOLING SYSTEM Capacity: 9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Change every 30000 miles/ 24 months	,

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.