TOYOTA (USA / CAN) AVALON XX30 AVALON 3.5 V6 24V (USA) GSX30 (2005-



2005)

Presteza MSP 5W-30	Asyntho 5W-30			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Normal		Moderate		
USE		CLIMATE		
ENGINE 2GR-FE Capacity: 6,1 liter (Service fill), Filter capacity: 0,4 liter				

Change every 5000 miles/ 6 months

TRANSAXLE AUTOMATIC U151E 5/1 Capacity: 8,8 liter (Dry fill), Capacity: 3,5 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 30000 miles/ 36 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 30000 miles/ 36 months, cha	nge every 60000 miles/ 72 months			

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Check every 15000 miles/ 18 months	·		

POWER STEERING				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
SP Matic 2032	ATF Almirol	ATF Dexron II-D		
Check every 15000 miles/ 18 month	hs	,		

PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) AVALON XX30 AVALON 3.5 V6 24V (USA) GSX30 (2005-



2005)

COOLING SYSTEM Capacity: 8,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months				
USE		CLIMATE		
First change only		Moderate		
r net enange emy		Moderate		
PRODUCT RECOMMENDATION 1		Moderate		
, , , , , , , , , , , , , , , , , , ,		Moderate		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.