

# TOYOTA (USA / CAN) CAMRY XV20 CAMRY

## 2.2 16V CNG (USA) SXV23 (1999-2001)

**ENGINE 5S-FNE**

Capacity: 3,6 liter (Service fill), Filter capacity: 0,2 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Asyntho 5W-30***Change every 7500 miles/ 6 months***USE**

Severe

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Asyntho 5W-30***Change every 5000 miles/ 4 months***DIFFERENTIAL FROM AUTOMATIC**

Capacity: 1,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol****PRODUCT RECOMMENDATION 3****ATF Dexron II-D***Check every 15000 miles/ 12 months***USE**

Severe

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol****PRODUCT RECOMMENDATION 3****ATF Dexron II-D***Change every 15000 miles/ 12 months***TRANSAXLE AUTOMATIC A140E 4/1**

Capacity: 2,5 liter (Service fill)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol****PRODUCT RECOMMENDATION 3****ATF Dexron II-D***Check every 15000 miles/ 12 months***USE**

Severe

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol****PRODUCT RECOMMENDATION 3****ATF Dexron II-D***Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months*

# TOYOTA (USA / CAN) CAMRY XV20 CAMRY 2.2 16V CNG (USA) SXV23 (1999-2001)



## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE                                       |  | CLIMATE  |
|---|--|----------|
| Normal                                    |  | Moderate |
| PRODUCT RECOMMENDATION 1                  |  |          |
| <b>Drauliquid DOT 3</b>                   |  |          |
| <i>Check every 15000 miles/ 12 months</i> |  |          |

## POWER STEERING

| USE                                       |                          | CLIMATE                  |
|---|--------------------------|--------------------------|
| Normal                                    |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>                      | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |
| <i>Check every 15000 miles/ 12 months</i> |                          |                          |

## COOLING SYSTEM

Capacity: 6,9 liter

| USE  |  | CLIMATE  |
|--|--|----------|
| Normal   |  | Moderate |
| PRODUCT RECOMMENDATION 1   |  |          |
| <b>Coolant SP 12 EVO</b>   |  |          |
| <i>Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months</i> |  |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.