

TOYOTA (USA / CAN) CAMRY XV20 CAMRY

3.0 V6 (USA) MCV20 (1999-2001)

**ENGINE 1MZ-FE**

Capacity: 4,7 liter (Service fill), Filter capacity: 0,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 7500 miles/ 6 months*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 5000 miles/ 4 months***TRANSAXLE AUTOMATIC A541E 4/1**

Capacity: 4,75 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

PRODUCT RECOMMENDATION 3

ATF Dexron II-D*Check every 15000 miles/ 12 months*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

PRODUCT RECOMMENDATION 3

ATF Dexron II-D*Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months***TRANSAXLE MANUAL 5/1**

Capacity: 4,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 15000 miles/ 12 months*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months*

TOYOTA (USA / CAN) CAMRY XV20 CAMRY

3.0 V6 (USA) MCV20 (1999-2001)



HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE | | CLIMATE |
|---|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |
| <i>Check every 15000 miles/ 12 months</i> | | |

POWER STEERING

| USE | | CLIMATE |
|---|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |
| <i>Check every 15000 miles/ 12 months</i> | | |

COOLING SYSTEM

Capacity: 9,1 liter

| USE | | CLIMATE |
|--|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 12 EVO | | |
| <i>Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months</i> | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.