TOYOTA (USA / CAN) HIGHLANDER XU20 HIGHLANDER HYBRID 4WD (USA) MHU28



(2005-2006)

ENGINE 3MZ-FE Capacity: 5,5 liter (Dry fill), Capacity: 4,7 liter (Service fill), Filter capacity: 0,2 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Presteza MSP 5W-30	Asyntho 5W-30			

Change every 5000 miles/ 6 months

DIFFERENTIAL REAR ELECTRIC DRIVE Q211 Capacity: 2 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 30000 miles/ 36 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months				

TRANSAXLE CVT P310 1/1 Capacity: 3,9-4,2 liter			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 30000 miles/ 36 months			
USE	CLIMATE		
Severe	Moderate		
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months			

PRODUCT RECOMMENDATION

HYDRAULIC BRAKE SYSTEM

TOYOTA (USA / CAN) HIGHLANDER XU20 HIGHLANDER HYBRID 4WD (USA) MHU28



CLIMATE

(2005-2006)

INOIIIIai		Moderate			
PRODUCT RECOMMENDATION 1					
Drauliquid DOT 3					
Check every 5000 miles/ 6 months	Check every 5000 miles/ 6 months				
COOLING SYSTEM Capacity: 10,3 liter, Capacity: 11,6 liter (with rear heater)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1					
Coolant SP 14+					
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months					
USE		CLIMATE			
First change only		Moderate			
PRODUCT RECOMMENDATION 1					
Coolant SP 14+					
Check every 15000 miles/ 18 months, char	nge every 100000 miles/ 120 months				
COOLING SYSTEM ELECTRIC DRIVE Capacity: 3,4 liter					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1					
Coolant SP 14+					
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months					
USE		CLIMATE			
First change only		Moderate			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months