TOYOTA (USA / CAN) HIGHLANDER XU50 HIGHLANDER 2.7 16V (USA) ASU50 (2014-



2019)

ENGINE 1AR-FE Capacity: 5,5 liter (Dry fill), Capacity: 4,4 lit	ear (Sarvice fill) Filter capacity: 0.4 liter		
USE	er (Service IIII), i liter capacity. 0,4 liter	CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Presteza MSP 0W-20			
Change every 10000 miles/ 12 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
Presteza MSP 0W-20			
Change every 5000 miles/ 6 months			
TRANSAXLE AUTOMATIC U760E 6/1 Capacity: 6,5 liter (Dry fill), Capacity: 3,2 lit	er (Service fill)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 30000 miles/ 36 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months			
HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Check every 5000 miles/ 6 months			

PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) HIGHLANDER XU50 HIGHLANDER 2.7 16V (USA) ASU50 (2014-



2019)

	CLIMATE		
	Moderate		
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months			
	CLIMATE		
	Moderate		
	nge every 50000 miles/ 60 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.