PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) HIGHLANDER XU50 HIGHLANDER 3.5 V6 24V 2WD (USA) GSU50 (2014-2016)

ENGINE 2GR-FE

Capacity: 7,1 liter (Dry fill), Capacity: 6,1 liter (Service fill), Filter capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		

Change every 10000 miles/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		

Change every 5000 miles/ 6 months

TRANSAXLE AUTOMATIC U660E 6/1

Capacity: 6,5 liter (Dry fill), Capacity: 3,2 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 30000 miles/ 36 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 5000 miles/ 6 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) HIGHLANDER XU50 HIGHLANDER 3.5 V6 24V 2WD (USA) GSU50 (2014-2016)

COOLING SYSTEM
Capacity: 10,9-11,6 liter, Capacity: 11,2-11,9 liter (with towing package)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months		

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367