TOYOTA (USA / CAN) PRIUS XW10 PRIUS (USA) NHW11 (2002-2003)



ENGINE 1NZ-FXE Capacity: 4,1 liter (Dry fill), Capacity: 3,7 liter (Service fill), Filter capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 7500 miles/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 5000 miles/ 6 months		

Change every 5000 miles/ 6 months

TRANSAXLE CVT 1/1 Capacity: 4,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Check every 30000 miles/ 24 months	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 15000 miles / 12 months	-

Oncon every	10000 111103/	12 111011011	

COOLING SYSTEM Capacity: 4,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		
Check every 15000 miles/ 12 months, char	every 30000 miles/ 24 months	

TOYOTA (USA / CAN) PRIUS XW10 PRIUS (USA) NHW11 (2002-2003)



COOLING SYSTEM ELECTRIC DRIVE Capacity: 2,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Chaoli avan (15000 miles/10 months, char	

Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.