PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) RAV4 XA20 RAV4 2.0 16V VVT-I 4WD (USA) ACA21 (2002-2002)

ENGINE 1AZ-FE
Capacity: 4,9 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

Change every 7500 miles/ 6 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

Change every 5000 miles/ 4 months

DIFFERENTIAL REAR
Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Check every 15000 miles/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	**Gearlube RPC 75W-80**	**SP Gear 1071**

Check every 15000 miles/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Change every 15000 miles/ 12 months

USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	**Gearlube RPC 75W-80**	**SP Gear 1071**

Change every 15000 miles/ 12 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) RAV4 XA20 RAV4 2.0 16V VVT-I 4WD (USA) ACA21 (2002-2002)

TRANSAXLE AUTOMATIC U140F 4/1
Capacity: 8,3 liter (Dry fill), Capacity: 3,9 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 30000 miles/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 30000 miles/ 24 months, change every 60000 miles/ 48 months

TRANSAXLE MANUAL 5/1
Capacity: 3,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Syngear 75W-90**

Check every 30000 miles/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Syngear 75W-90**

Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) RAV4 XA20 RAV4 2.0 16V VVT-I 4WD (USA) ACA21 (2002-2002)

TRANSFERBOX
Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
Check every 15000 miles/ 12 months		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	**Gearlube RPC 75W-80**	**SP Gear 1071**
Check every 15000 miles/ 12 months		

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
Change every 15000 miles/ 12 months		

USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	**Gearlube RPC 75W-80**	**SP Gear 1071**
Change every 15000 miles/ 12 months		

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 15000 miles/ 12 months		

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 15000 miles/ 12 months		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) RAV4 XA20 RAV4 2.0 16V VVT-I 4WD (USA) ACA21 (2002-2002)

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

Check every 15000 km/ 12 months

COOLING SYSTEM

Capacity: 6,2 liter (with automatic transmission), Capacity: 6,3 liter (with manual transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367