

TOYOTA (USA / CAN) RAV4 XA30 RAV4 3.5 V6 24V 4WD (USA) GSA33 (2006-2008)

**ENGINE 2GR-FE**

Capacity: 6,8 liter (Dry fill), Capacity: 6,1 liter (Service fill), Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30*Change every 5000 miles/ 6 months***DIFFERENTIAL REAR**

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 15000 miles/ 18 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Check every 15000 miles/ 18 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 15000 miles/ 18 months*

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Change every 15000 miles/ 18 months*

TOYOTA (USA / CAN) RAV4 XA30 RAV4 3.5 V6 24V 4WD (USA) GSA33 (2006-2008)

**TRANSAXLE AUTOMATIC U151F 5/1**

Capacity: 9 liter (Dry fill), Capacity: 3,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 30000 miles/ 36 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

*Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months***TRANSFERBOX**

Capacity: 0,45 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Check every 15000 miles/ 18 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

*Change every 15000 miles/ 18 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 5000 miles/ 6 months

TOYOTA (USA / CAN) RAV4 XA30 RAV4 3.5 V6 24V 4WD (USA) GSA33 (2006-2008)

**COOLING SYSTEM**

Capacity: 8,9 liter, Capacity: 9,3 liter (with towing package)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.