

TOYOTA (USA / CAN) SIENNA XL20 SIENNA 3.3 V6 24V 2WD (USA) MCL20 (2004-2004)

**ENGINE 3MZ-FE**

Capacity: 5,5 liter (Dry fill), Capacity: 4,7 liter (Service fill), Filter capacity: 0,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30*Change every 7500 miles/ 6 months*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30*Change every 5000 miles/ 4 months***TRANSAXLE AUTOMATIC U151E 5/1**

Capacity: 8,8 liter (Dry fill), Capacity: 3,5 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Check every 30000 miles/ 24 months*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Check every 30000 miles/ 24 months, change every 60000 miles/ 48 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 15000 miles/ 12 months*

TOYOTA (USA / CAN) SIENNA XL20 SIENNA 3.3 V6 24V 2WD (USA) MCL20 (2004-2004)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 15000 miles/ 12 months

COOLING SYSTEM

Capacity: 11,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.