

# TOYOTA (USA / CAN) SIENNA XL20 SIENNA

## 3.5 V6 24V 4WD (USA) GSL25 (2007-2010)

**ENGINE 2GR-FE**

Capacity: 6,8 liter (Dry fill), Capacity: 6,1 liter (Service fill), Filter capacity: 0,4 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Presteza MSP 5W-30***Change every 5000 miles/ 6 months***DIFFERENTIAL REAR**

Capacity: 0,9 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 80W-90***Check every 15000 miles/ 18 months***USE**

Normal

**CLIMATE**

Arctic

**PRODUCT RECOMMENDATION 1****SP Gear 5015****PRODUCT RECOMMENDATION 2****Gearlube RPC 75W-80****PRODUCT RECOMMENDATION 3****SP Gear 1071***Check every 15000 miles/ 18 months***USE**

Severe

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 80W-90***Change every 15000 miles/ 18 months***USE**

Severe

**CLIMATE**

Arctic

**PRODUCT RECOMMENDATION 1****SP Gear 5015****PRODUCT RECOMMENDATION 2****Gearlube RPC 75W-80****PRODUCT RECOMMENDATION 3****SP Gear 1071***Change every 15000 miles/ 18 months*

# TOYOTA (USA / CAN) SIENNA XL20 SIENNA

## 3.5 V6 24V 4WD (USA) GSL25 (2007-2010)



**TRANSAXLE AUTOMATIC U151F 5/1**  
Capacity: 9 liter (Dry fill), Capacity: 3,6 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>SP Matic 4036</b>     |  |  |

Check every 30000 miles/ 36 months

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>SP Matic 4036</b>     |  |  |

Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months

**TRANSFERBOX**  
Capacity: 0,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                             |  |  |
|-----------------------------|--|--|
| PRODUCT RECOMMENDATION 1    |  |  |
| <b>Gearlube GL-5 80W-90</b> |  |  |

Check every 15000 miles/ 18 months

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

|                          |                            |                          |
|--------------------------|----------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> | <b>SP Gear 1071</b>      |

Check every 15000 miles/ 18 months

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

|                             |  |  |
|-----------------------------|--|--|
| PRODUCT RECOMMENDATION 1    |  |  |
| <b>Gearlube GL-5 80W-90</b> |  |  |

Change every 15000 miles/ 18 months

| USE    | CLIMATE |
|--------|---------|
| Severe | Arctic  |

|                          |                            |                          |
|--------------------------|----------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> | <b>SP Gear 1071</b>      |

Change every 15000 miles/ 18 months

# TOYOTA (USA / CAN) SIENNA XL20 SIENNA 3.5 V6 24V 4WD (USA) GSL25 (2007-2010)



## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

Check every 5000 miles/ 6 months

## POWER STEERING

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |

Check every 5000 miles/ 6 months

## COOLING SYSTEM

Capacity: 11,3 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| First change only        |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.