

VAUXHALL ANTARA L07 ANTARA 3.2 V6 4X4 (2006-2011)



ENGINE Z32SE
Capacity: 7,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Helar MSP+ 5W-40

PRODUCT RECOMMENDATION 3

Specialsynth MSP 5W-40

Change every 30000 km/ 12 months

DIFFERENTIAL REAR
Capacity: 0,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

TRANSAXLE AUTOMATIC 5/1
Capacity: 6,85 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

TRANSFERBOX
Capacity: 0,8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

HYDRAULIC BRAKE SYSTEM
Capacity: 0,67 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Check every 12 months, change every 48 months

VAUXHALL ANTARA L07 ANTARA 3.2 V6 4X4 (2006-2011)



HYDRAULIC CLUTCH SYSTEM

Capacity: 0,06 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 12 months, change every 48 months

POWER STEERING

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 12 months/ 30000 km

COOLING SYSTEM

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 30000 km/ 12 months, change every 240000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.