VAUXHALL ASTRA / BELMONT T85 ASTRA / BELMONT 1.6 D (1987-1991)



| ENGINE 16DA Capacity: 5 liter | | |
|----------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Bi-Turbo 20W-50 | | |
| Change every 7500 km/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Emperol Racing 10W-60 | Emperol 10W-40 | Bi-Turbo 15W-40 |
| Change every 7500 km/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Asyntho 5W-30 | | |
| Change every 7500 km/ 12 months | | |
| USE | | CLIMATE |
| Severe | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Bi-Turbo 20W-50 | | |
| Change every 7500 km/ 6 months | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Emperol Racing 10W-60 | Emperol 10W-40 | Bi-Turbo 15W-40 |
| Change every 7500 km/ 6 months | | |
| USE | | CLIMATE |
| Severe | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Asyntho 5W-30 | | |
| Change every 7500 km/ 6 months | | |

VAUXHALL ASTRA / BELMONT T85 ASTRA / BELMONT 1.6 D (1987-1991)



| TRANSAXLE AUTOMATIC 3/1 Capacity: 7 liter | |
|--|---------------------|
| use Normal | climate Moderate |
| PRODUCT RECOMMENDATION 1 ATF Dexron II-D | |

Check every 7500 km/ 12 months, change every 45000 km/ 48 months

| | CLIMATE |
|--------------------------|----------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W | |
| | |

Check every 7500 km/ 6 months

| HYDRAULIC BRAKE SYSTEM | | |
|---------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| | : | : |

Change every 12 months

| POWER STEERING | | |
|--------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |

| COOLING SYSTEM Capacity: 7,6 liter | |
|---------------------------------------|---------------------------------------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |
| 01 0.1 11 | · · · · · · · · · · · · · · · · · · · |

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.