VAUXHALL ASTRA G CABRIO T98 ASTRA G CABRIO 2.2 (2001-2005)



ENGINE Z22SE Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30
Change every 30000 km/ 12 month	es .	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30
Change every 30000 km/ 6 months	·	'

TRANSAXLE AUTOMATIC AF 22 4/1 Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Check every 12 months/ 30000 km	· ·

TRANSAXLE MANUAL F23 5/1 Capacity: 1,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90
Check every 24 months/ 30000 km	,	1

HYDRAULIC ACTUATION CONVERTIBLE ROOF		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		

VAUXHALL ASTRA G CABRIO T98 ASTRA G CABRIO 2.2 (2001-2005)



Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
HYDRAULIC BRAKE/CLUTCH SYSTEM		

Check every 30000 km/ 12 months, change every 24 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 24 months/ 30000 km	

COOLING SYSTEM Capacity: 6,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Check every 24 months/ 30000 km	,	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.