VAUXHALL ASTRA G T98 ASTRA G 1.6 (62 KW) (2000-2004)



| ENGINE Z16SE Capacity: 3,5 liter, Filter capacity: 0 | ,4 liter | |
|----------------------------------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40 | Emperol 5W-40 | Asyntho 5W-30 |
| Change every 30000 km/ 12 month | IS | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40 | Emperol 5W-40 | Asyntho 5W-30 |
| Changes avery 20000 line (Changester | | 1 |

Change every 30000 km/ 6 months

| TRANSAXLE AUTOMATIC AF 13-II 4/1 Capacity: 3 liter | |
|-------------------------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 4026 | |
| Check every 24 months/ 30000 km | |

| TRANSAXLE MANUAL F13 5/1 Capacity: 1,6 liter | | |
|-------------------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | SP Gear 5015 | Syngear TDL 75W-90 |

Check every 24 months/ 30000 km

| HYDRAULIC BRAKE/CLUTCH SYSTEM | | | |
|-------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| Change every 24 months | · · | · | |

VAUXHALL ASTRA G T98 ASTRA G 1.6 (62 KW) (2000-2004)



| POWER STEERING | |
|---------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Fluid 3013 | |
| Charles avery 24 magnifies (20000 kmg | |

Check every 24 months/ 30000 km

| COOLING SYSTEM Capacity: 5,9 liter, Capacity: 6,2 liter (+ airconditioning) | | | |
|--------------------------------------------------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15 | Coolant SP 15+ | | |
| Check every 24 months/ 30000 km | · | · | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.