

VAUXHALL CAVALIER III J89 CAVALIER 2.5 V6 (1993-1995)

**ENGINE**

Capacity: 4,5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Change every 15000 km/ 12 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar 0W-40****PRODUCT RECOMMENDATION 2****Emperol 5W-40****PRODUCT RECOMMENDATION 3****Emperol Racing 10W-60***Change every 15000 km/ 12 months***USE**

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Change every 15000 km/ 6 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar 0W-40****PRODUCT RECOMMENDATION 2****Emperol 5W-40****PRODUCT RECOMMENDATION 3****Emperol Racing 10W-60***Change every 15000 km/ 6 months***TRANSAXLE AUTOMATIC** Aisin Warner 4/1

Capacity: 3,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D***Check every 15000 km/ 12 months***TRANSAXLE MANUAL** 5/1

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 5015****PRODUCT RECOMMENDATION 2****Gearlube GL-4 80W***Check every 15000 km/ 12 months*

VAUXHALL CAVALIER III J89 CAVALIER 2.5 V6 (1993-1995)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 12 months

POWER STEERING

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.