## **VAUXHALL CORSA C X01 CORSA C 1.8 16V** (2004-2006)



| ENGINE Z18XE<br>Capacity: 4,5 liter |                          |                          |
|-------------------------------------|--------------------------|--------------------------|
| USE                                 |                          | CLIMATE                  |
| Flexible (max)                      |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Presteza MSP 5W-30                  | Helar MSP+ 5W-40         | Specialsynth MSP 5W-40   |
|                                     |                          |                          |

Change every 30000 km/ 24 months

| <b>TRANSAXLE MANUAL</b> 5/1<br>Capacity: 1,6 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
|  |                          |                          |
| PRODUCT RECOMMENDATION 1                           | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |

| HYDRAULIC BRAKE SYSTEM    |                          |          |  |  |
|---------------------------|--------------------------|----------|--|--|
| USE                       |                          | CLIMATE  |  |  |
| Normal                    |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |  |  |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4       |          |  |  |
|                           |                          |          |  |  |

Change every 24 months

| POWER STEERING           |  |          |
|--------------------------|--|----------|
| USE                      |  | CLIMATE  |
| Flexible (max)           |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| ATF Dexron II-D          |  |          |
|                          |  |          |

Check every 24 months/ 30000 km

| COOLING SYSTEM<br>Capacity: 5,3 liter |                          |          |
|---------------------------------------|--------------------------|----------|
| USE                                   |                          | CLIMATE  |
| Flexible (max)                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1              | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15                         | Coolant SP 15+           |          |
| Check every 24 months/ 30000 km       |                          |          |

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.