

# VAUXHALL INSIGNIA A G09 INSIGNIA A 2.0 SIDI TURBO (184 KW) 4X4 (2013-2015)



**ENGINE** A20NHT, B20NHT (LTG)  
Capacity: 5,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|-----------------------------|---------------------------|--------------------------|
| <b>Helar SP LL-03 5W-30</b> | <b>Presteza MSP 5W-30</b> | <b>Xedoz FE 5W-30</b>    |

*Change every 30000 km/ 12 months*

**DIFFERENTIAL REAR** (4x4)  
Capacity: 0,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

**TRANSAXLE AUTOMATIC** 6T70 6/1  
Capacity: 9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Matic 4036</b>     |  |  |

*Change every 80000 km/ 72 months*

**TRANSAXLE MANUAL** F40 6/1  
Capacity: 1,8 liter (Dry fill), Capacity: 1,6 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Gear 1081</b>      |  |  |

## TRANSFERBOX

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Gear 1011</b>      |  |  |

# VAUXHALL INSIGNIA A G09 INSIGNIA A 2.0 SIDI TURBO (184 KW) 4X4 (2013-2015)



## HALDEX-CLUTCH

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 6033</b>     |  |          |

## HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE                              |  | CLIMATE  |
|----------------------------------|--|----------|
| Normal                           |  | Moderate |
| PRODUCT RECOMMENDATION 1         |  |          |
| <b>Drauliquid-LV Super DOT 4</b> |  |          |

*Change every 60000 km/ 24 months*

| USE                              |  | CLIMATE  |
|----------------------------------|--|----------|
| First change only                |  | Moderate |
| PRODUCT RECOMMENDATION 1         |  |          |
| <b>Drauliquid-LV Super DOT 4</b> |  |          |

*Change every 30000 km/ 12 months*

## POWER STEERING

Capacity: 0-0 liter (Between min and max.)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4036</b>     |  |          |

*Check every 12 months/ 30000 km*

## COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15</b>     | <b>Coolant SP 15+</b>    |          |

*Check every 12 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.