
## **VAUXHALL SENATOR B V88 SENATOR 2.5I**






| ISE                              |                          | CLIMATE                  |
|----------------------------------|--------------------------|--------------------------|
| Normal                           |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1         |                          |                          |
| Bi-Turbo 20W-50                  |                          |                          |
| Check every 500 hours, change ev | very 15000 km/ 12 months |                          |
| USE                              |                          | CLIMATE                  |
| Normal                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40                      | Emperol 5W-40            | Emperol Racing 10W-60    |
| Check every 500 hours, change ev | very 15000 km/ 12 months | -                        |
| USE                              |                          | CLIMATE                  |
| Severe                           |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1         |                          |                          |
| Bi-Turbo 20W-50                  |                          |                          |
| Check every 500 hours, change ev | very 15000 km/ 6 months  |                          |
| USE                              |                          | CLIMATE                  |
| Severe                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40                      | Emperol 5W-40            | Emperol Racing 10W-60    |
| Check every 500 hours, change ev | very 15000 km/ 6 months  | <u> </u>                 |

| DIFFERENTIAL REAR Capacity: 1,2 liter |          |
|---------------------------------------|----------|
| USE                                   | CLIMATE  |
| Normal                                | Moderate |
| PRODUCT RECOMMENDATION 1              |          |
| Gearlube LS 80W-90                    |          |
| Check every 15000 km/ 12 months       |          |

Check every 15000 km/ 12 months

| DIFFERENTIAL REAR LIMITED SLIP  |  |          |
|---------------------------------|--|----------|
| USE                             |  | CLIMATE  |
| Normal                          |  | Moderate |
| PRODUCT RECOMMENDATION 1        |  |          |
| Gearlube LS 80W-90              |  |          |
| Check every 15000 km/ 12 months |  |          |

## **VAUXHALL SENATOR B V88 SENATOR 2.51**





| TRANSMISSION AUTOMATIC 4/1 Capacity: 5,5 liter |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                       |          |
| ATF Dexron II-D                                |          |
| Change every 36 months                         |          |

| TRANSMISSION MANUAL 5/1<br>Capacity: 1,9 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011                                   | SP Gear 5015             | Syngear TDL 75W-90       |

Check every 15000 km/ 12 months

| HYDRAULIC BRAKE SYSTEM    |                          |          |
|---------------------------|--------------------------|----------|
| USE                       |                          | CLIMATE  |
| Normal                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4       |          |
| Change every 12 months    | '                        | '        |

| POWER STEERING           |          |  |
|--------------------------|----------|--|
| USE                      | CLIMATE  |  |
| Normal                   | Moderate |  |
| PRODUCT RECOMMENDATION 1 |          |  |
| ATF Dexron II-D          |          |  |

| COOLING SYSTEM Capacity: 10,1-10,3 liter |          |
|--|----------|
| USE                                      | CLIMATE  |
| Normal                                   | Moderate |
| PRODUCT RECOMMENDATION 1                 |          |
| Coolant -38 Organic NF                   |          |
| Change every 24 months                   | '        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.