VAUXHALL VIVA C16 VIVA 1.0 (2015-2018)



ENGINE B10XE (L5Q) Capacity: 3,5 liter (Service fill, vehicles built from VIN HC789341), Capacity: 4 liter (Service fill, vehicles built up to VIN HC789340)			
use Normal		climate Moderate	
PRODUCT RECOMMENDATION 1 Presteza MSP 0W-20	PRODUCT RECOMMENDATION 2 Duranza MSP ECO 0W-20	PRODUCT RECOMMENDATION 3 Avanza MSP 0W-20	

Change every 30000 km/ 12 months

TRANSAXLE MANUAL Y4M 5/1 Capacity: 1,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Check every 30000 km/ 12 months, change every 1	150000 km/ 120 months

TRANSAXLE SEMI-AUTOMATIC Y4M MTA 5/1			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Gear 5015			

Check every 30000 km/12 months, change every 150000 km/120 months

HYDRAULIC ACTUATION CLUTCH Capacity: 0,55-0,6 liter	I AND SHIFT MODULE		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Fluid 3023			

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	

VAUXHALL VIVA C16 VIVA 1.0 (2015-2018)



COOLING SYSTEM Capacity: 4,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Check every 12 months/ 30000 km	•	,

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.