

VAUXHALL ZAFIRA B A05 ZAFIRA B 1.8 (88 KW) (2013-2014)



ENGINE A18XEL
Capacity: 4,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30

PRODUCT RECOMMENDATION 2

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 3

Xedoz FE 5W-30

Change every 30000 km/ 12 months

TRANSAXLE MANUAL F17+ 5/1
Capacity: 1,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS
Capacity: 0,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 30000 km/ 12 months, change every 24 months

POWER STEERING
Capacity: 0,69 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

COOLING SYSTEM
Capacity: 6,1 liter, Capacity: 6,3 liter (+ airconditioning)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15

PRODUCT RECOMMENDATION 2

Coolant SP 15+

Check every 12 months/ 30000 km

PRODUCT RECOMMENDATION

VAUXHALL ZAFIRA B A05 ZAFIRA B 1.8 (88 KW) (2013-2014)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.