

VAUXHALL ZAFIRA C P12 ZAFIRA C 2.0 BITURBO CDTI (143 KW) (2013-2015)



MOTOR A20DTR (LBY)

Kapacitet: 4,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

PRODUKTANBEFALING 2

Presteza MSP 5W-30

Skift alle 30000 km/ 12 måneder

TRANSAKSEL MANUEL F40 6/1

Kapacitet: 1,6 liter (Servicepåfyldning), Kapacitet: 1,8 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Skift alle 60000 km/ 24 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Skift alle 30000 km/ 12 måneder

SERVOSTYRING

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 12 måneder/ 30000 km

VAUXHALL ZAFIRA C P12 ZAFIRA C 2.0 BITURBO CDTI (143 KW) (2013-2015)

**KØLESYSTEM**

Kapacitet: 9 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15

PRODUKTANBEFALING 2

Coolant SP 15+*Kontroller alle 12 måneder/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.