

VAUXHALL ZAFIRA C P12 ZAFIRA C 1.4 TURBO (103 KW) (2014-2018)



ENGINE B14NET (LUJ)
Capacity: 4 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Xedoz FE 5W-30

Change every 30000 km/ 12 months

TRANSAXLE AUTOMATIC 6T40/6T45/6T50 6/1
Capacity: 8-8,5 liter (Dry fill), Capacity: 4-6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 12 months/ 30000 km

TRANSAXLE MANUAL M32 6/1
Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 1081		

Check every 12 months/ 30000 km

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

COOLING SYSTEM
Capacity: 6,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

PRODUCT RECOMMENDATION

VAUXHALL ZAFIRA C P12 ZAFIRA C 1.4 TURBO (103 KW) (2014-2018)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.