

# VAUXHALL ZAFIRA C P12 ZAFIRA C 1.6 CDTI (88 KW) (2014-2018)

**ENGINE B16DTJ**

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Helar SP LL-03 5W-30**

PRODUCT RECOMMENDATION 2

**Presteza MSP 5W-30***Change every 30000 km/ 12 months***TRANSAXLE MANUAL F40 6/1**

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1081****HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4***Change every 60000 km/ 24 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4***Change every 30000 km/ 12 months***POWER STEERING**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 12 months/ 30000 km*

# VAUXHALL ZAFIRA C P12 ZAFIRA C 1.6 CDTI (88 KW) (2014-2018)



## COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15</b>	<b>Coolant SP 15+</b>	

Check every 12 months/ 30000 km

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*