

VOLKSWAGEN (VW) (EU) BEETLE 5C BEETLE 2.0 TDI (110 KW) (2014-2018)



MOTOR CUUB

Kapacitet: 4,7 liter (Servicepåfyldning)

ANVEND

Forlænget interval (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Skift alle 30000 km/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Skift alle 15000 km/ 12 måneder

TRANSAKSEL HALVAUTOMATISK DSG 02E (DQ250) 6/1

Kapacitet: 6,9-7,2 liter (Førstegangsopfyldning), Kapacitet: 5,2 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2072

Skift alle 60000 km

TRANSAKSEL MANUEL 02Q 6/1

Kapacitet: 2,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

Kontroller alle 48 måneder/ 60000 km

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 1-1,15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Skift alle 24 måneder

VOLKSWAGEN (VW) (EU) BEETLE 5C BEETLE 2.0 TDI (110 KW) (2014-2018)



KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Kontroller alle 48 måneder/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.