

VOLKSWAGEN (VW) (EU) CADDY KOMBI SA CADDY COMBI 1.6 TDI (75 KW) DPF (2015-2020)



MOTOR CAYD

Kapacitet: 4,3 liter (Servicepåfyldning)

ANVEND

Forlænget interval (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

Skift alle 30000 km/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

Skift alle 15000 km/ 12 måneder

TRANSAKSEL HALVAUTOMATISK DSG 0AM (DQ200) 7/1

Kapacitet: 1,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

Kontroller alle 24 måneder/ 30000 km

TRANSAKSEL MANUEL 0A4 5/1

Kapacitet: 1,8-2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

Kontroller alle 24 måneder/ 30000 km

HYDRAULISK AKTIVERING GEARCASE

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

VOLKSWAGEN (VW) (EU) CADDY KOMBI SA CADDY COMBI 1.6 TDI (75 KW) DPF (2015-2020)



HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 1,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Kontroller alle 30000 km/ 24 måneder, skift alle 24 måneder

KØLESYSTEM FRA OG MED PRODUKTIONS DATO 25-11-2019

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Kontroller alle 48 måneder/ 60000 km

KØLESYSTEM OP TIL PRODUKTIONS DATO 25-11-2019

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Kontroller alle 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.