

# VOLKSWAGEN (VW) (EU) CC 358 CC 2.0 TFSI (147 KW) KOR (2011-2017)



**MOTOR** CAWB, CBFA, CCTA, CCZA  
Kapacitet: 4,7 liter (Servicepåfyldning)

ANVEND

Forlænget interval (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

**Helar SP LL-03 0W-30**

PRODUKTANBEFALING 2

**Helar SP LL-03 5W-30**

*Skift alle 30000 km/ 24 måneder*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Helar 0W-40**

PRODUKTANBEFALING 2

**Emperol 5W-40**

PRODUKTANBEFALING 3

**Asyntho 5W-30**

*Skift alle 15000 km/ 12 måneder*

**TRANSAKSEL HALVAUTOMATISK** DSG 02E (DQ250) 6/1  
Kapacitet: 5,2 liter (Servicepåfyldning), Kapacitet: 6,9-7,2 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Matic 2072**

*Skift alle 60000 km*

**TRANSAKSEL MANUEL** 02Q 6/1  
Kapacitet: 2,15 liter (Servicepåfyldning), Kapacitet: 2,3 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Gear 1081**

PRODUKTANBEFALING 2

**SP Gear 5015**

*Kontroller alle 60000 km/ 36 måneder*

## HYDRAULISK AKTIVERING GEARCASE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Fluid 3013**

# VOLKSWAGEN (VW) (EU) CC 358 CC 2.0 TFSI (147 KW) KOR (2011-2017)



## HYDRAULISK BREMSESYSTEM

Kapacitet: 1-1,15 liter

| ANVEND                           |  | KLIMA   |
|----------------------------------|--|---------|
| Normal                           |  | Moderat |
| PRODUKTANBEFALING 1              |  |         |
| <b>Drauliquid-LV Super DOT 4</b> |  |         |

Kontroller alle 30000 km/ 24 måneder, skift alle 24 måneder

## ELEKTRO-HYDRAULISK SERVOSTYRING

Kapacitet: 0-0 liter (Imellem min. og max.)

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>SP Fluid 3013</b> |  |         |

Kontroller alle 24 måneder/ 30000 km

## KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

| ANVEND                   |  | KLIMA   |
|--------------------------|--|---------|
| Normal                   |  | Moderat |
| PRODUKTANBEFALING 1      |  |         |
| <b>Coolant SP 12 EVO</b> |  |         |

Kontroller alle 48 måneder/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.