

VOLKSWAGEN (VW) (EU) EOS 1F7 EOS 2.0 16V TFSI (155 KW) (2009-2010)



MOTOR CCZB

Kapacitet: 4,6 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Forlænget interval (max)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Skift alle 30000 km/ 24 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

TRANSAKSEL HALVAUTOMATISK DSG 02E (DQ250) 6/1

Kapacitet: 5,2 liter (Servicepåfyldning), Kapacitet: 7,2 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2072		

Skift alle 60000 km

TRANSAKSEL MANUEL 02Q 6/1

Kapacitet: 2,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1081	SP Gear 5015	

HYDRAULISK AKTIVERING GEARCASSE

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3013		

VOLKSWAGEN (VW) (EU) EOS 1F7 EOS 2.0 16V TFSI (155 KW) (2009-2010)



HYDRAULISK AKTIVERING KALECHE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Kontroller alle 48 måneder/ 60000 km

ELEKTRO-HYDRAULISK SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 12 EVO		

Kontroller alle 48 måneder/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.